

DOW CORNING CORPORATION
MATERIAL SAFETY DATA SHEET

DOW CORNING(R) 100x SILICONE SEALANT, CLEAR 8641

EMERGENCY TELEPHONE NO. (517) 496-5900 PAGE: 1

SECTION I - GENERAL INFORMATION

MANUFACTURER'S NAME: DOW CORNING CORP. PRODUCT INFORMATION NO. (517) 496-6000
ADDRESS: SOUTH SAGINAW ROAD, MIDLAND MI 48686

PROPER SHIPPING NAME(49CFR 172.101): NONE
D.O.T. HAZARD NAME(49CFR 172.101): NONE
D.O.T. ID NO(49CFR 172.101): NONE
D.O.T. HAZARD CLASS(49CFR 172.101): NONE
RCRA HAZARD CLASS(40CFR 261)(IF DISCARDED): NONE
E.P.A. PRIORITY POLLUTANTS(40CFR 122.53): NONE
NFPA = NATIONAL FIRE PROTECTION ASSOCIATION - 704
HEALTH (NFPA): 1 FLAMMABILITY (NFPA): 1 REACTIVITY (NFPA): 0
CAS NO: MIXTURE DOW CORNING WARNING CODE: NOT USED
GENERIC DESCRIPTION: SILICONE

SECTION II - HAZARDOUS INGREDIENTS AS DEFINED IN 29 CFR 1910.1200
(CARCINOGENS IDENTIFIED WITH AN ASTERISK *)

CAS NO.	INGREDIENT	WT. %	EXPOSURE LIMITS
004253343	METHYLTRIAACETOXYSILANE	2	SEE COMMENT BELOW.
017689779	ETHYLTRIAACETOXYSILANE	2	SEE COMMENT BELOW.
007631869	SILICA, AMORPHOUS	8	OSHA PEL: TWA 6 MG/M3 ACGIH TLV: TWA 10 MG/M3 TOTAL DUST

COMMENT: OBSERVE LIMITS FOR ACETIC ACID, FORMED DURING CURING ON EXPOSURE TO WATER OR HUMID AIR. OSHA PEL: TWA 10 PPM. ACGIH TLV: TWA 10 PPM, STEL 15 PPM.



DOW CORNING CORPORATION
MATERIAL SAFETY DATA SHEET

DOW CORNING(R) 100% SILICONE SEALANT, CLEAR

PAGE: 2

SECTION III - EFFECTS OF OVEREXPOSURE

EYE: DIRECT CONTACT IRRITATES SLIGHTLY TO MODERATELY WITH REDNESS AND SWELLING.

SKIN: A SINGLE SHORT EXPOSURE (LESS THAN 24 HOURS) MAY IRRITATE. REPEATED PROLONGED CONTACT (24 TO 48 HOURS) MAY IRRITATE MODERATELY.

INHALATION: VAPOR OVEREXPOSURE MAY IRRITATE EYES, NOSE AND THROAT.

ORAL: SMALL AMOUNTS TRANSFERRED TO THE MOUTH BY FINGERS DURING USE, ETC., SHOULD NOT INJURE. SWALLOWING LARGE AMOUNTS MAY CAUSE DIGESTIVE DISCOMFORT.

COMMENT: NO INJURY FROM SILICA DUSTS SHOULD OCCUR DURING REASONABLE USE. IF USE CREATES RESPIRABLE PARTICLES, SOME RESPIRATORY SYSTEM INJURY MAY OCCUR. THE ABOVE LISTED POTENTIAL EFFECTS OF OVEREXPOSURE ARE BASED ON ACTUAL DATA, RESULTS OF STUDIES PERFORMED UPON SIMILAR COMPOSITIONS, COMPONENT DATA AND/OR EXPERT REVIEW OF THE PRODUCT. OVEREXPOSURE TO ANY CHEMICAL MAY RESULT IN ENHANCEMENT OF PRE-EXISTING ADVERSE MEDICAL CONDITIONS AND ALLERGIC REACTIONS. WHEN HEATED TO TEMPERATURES ABOVE 150 DEGREES C IN THE PRESENCE OF AIR, PRODUCT CAN FORM FORMALDEHYDE VAPORS. FORMALDEHYDE IS A POTENTIAL CANCER HAZARD, A KNOWN SKIN AND RESPIRATORY SENSITIZER, AND AN IRRITANT TO THE EYES, NOSE, THROAT, SKIN, AND DIGESTIVE SYSTEM. SAFE HANDLING CONDITIONS MAY BE MAINTAINED BY KEEPING VAPOR CONCENTRATIONS WITHIN THE OSHA PERMISSIBLE EXPOSURE LIMIT FOR FORMALDEHYDE.

SECTION IV - EMERGENCY AND FIRST AID PROCEDURES

EYES: IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION.

SKIN: WIPE OFF AND FLUSH WITH WATER. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS.

INHALATION: REMOVE TO FRESH AIR.

ORAL: NO FIRST AID SHOULD BE NEEDED.

COMMENT: NONE

DOW CORNING CORPORATION
MATERIAL SAFETY DATA SHEET

DOW CORNING(R) 100X SILICONE SEALANT, CLEAR

PAGE: 3

SECTION V - FIRE AND EXPLOSION DATA

FLASH POINT (METHOD USED): OPEN CUP ABOVE 250F/120C
AUTOIGNITION: NOT DETERMINED

FLAMMABILITY LIMITS IN AIR : LOWER: N.D. UPPER: N.D.

EXTINGUISHING MEDIA: WATER WATER FOG X CO2 X DRY CHEMICAL X FOAM X OTHER

SPECIAL FIRE FIGHTING PROCEDURES, SELF-CONTAINED BREATHING APPARATUS AND
PROTECTIVE CLOTHING SHOULD BE WORN IN FIGHTING FIRES INVOLVING CHEMICALS

UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE.

COMMENTS: N.D. - NOT DETERMINED

SECTION VI - PHYSICAL DATA

BOILING POINT(AT 760 MM HG): NOT APPLICABLE

SPECIFIC GRAVITY (AT 77 DEG F/25 DEG C): 1.04

MELTING POINT: NOT APPLICABLE

VAPOR PRESSURE (AT 77 DEG F/25 DEG C): LESS THAN 5 MM

VAPOR DENSITY (AIR = 1 AT 77 DEG F/25 DEG C): NOT APPLICABLE

PERCENT VOLATILE BY WEIGHT (x): LESS THAN 5

EVAPORATION RATE (ETHER = 1): NOT APPLICABLE

SOLUBILITY IN WATER(x): LESS THAN 0.1

ODOR, APPEARANCE, COLOR: ACETIC ACID-LIKE ODOR, PASTE, CLEAR.

NOTE: THE ABOVE INFORMATION IS NOT INTENDED FOR USE IN PREPARING PRODUCT
SPECIFICATIONS. CONTACT DOW CORNING BEFORE WRITING SPECIFICATIONS.



DOW CORNING CORPORATION
MATERIAL SAFETY DATA SHEET

DOW CORNING(R) 100% SILICONE SEALANT, CLEAR

PAGE: 4

SECTION VII - REACTIVITY DATA

STABILITY: STABLE

INCOMPATIBILITY(MATERIAL TO AVOID): OXIDIZING MATERIAL CAN CAUSE A REACTION. WATER OR HUMID AIR CAUSES CURING AND ACETIC ACID VAPORS FORM.

CONDITIONS TO AVOID: EXPOSURE TO ABOVE UNTIL READY TO USE.

HAZARDOUS DECOMPOSITION PRODUCTS: SILICON DIOXIDE, CARBON DIOXIDE, AND TRACES OF INCOMPLETELY BURNED CARBON PRODUCTS, INCLUDES FORMALDEHYDE.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

CONDITIONS TO AVOID: NOT APPLICABLE.

COMMENTS: NONE

SECTION VIII - SPILL, LEAK, MAINTENANCE/REPAIR AND DISPOSAL PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: REMOVE PRODUCT AND CONTAIN FOR SALVAGE OR DISPOSAL.

PROTECTIVE EQUIPMENT:
EYES: USE PROPER PROTECTION -- SAFETY GLASSES, AS A MINIMUM.

SKIN: WASHING AT MEALTIME AND END OF SHIFT IS ADEQUATE. REMOVE CONTAMINATED CLOTHING AS SOON AS PRACTICAL AND CLEAN THOROUGHLY BEFORE REUSE.

INHALATION: USE RESPIRATORY PROTECTION UNLESS LOCAL EXHAUST VENTILATION IS ADEQUATE OR AIR SAMPLING DATA SHOWS EXPOSURES ARE WITHIN TLV AND PEL GUIDELINES.

WASTE DISPOSAL METHOD: DOW CORNING SUGGESTS THAT ALL LOCAL, STATE AND FEDERAL REGULATIONS CONCERNING HEALTH AND POLLUTION BE REVIEWED TO DETERMINE APPROVED DISPOSAL PROCEDURES. CONTACT DOW CORNING IF THERE ARE ANY DISPOSAL QUESTIONS.

D.O.T. (49CFR 171.8)/E.P.A. (40CFR 117) SPILL REPORTING INFORMATION
HAZARDOUS SUBSTANCE: NONE REPORTABLE QUANTITY: NOT APPLICABLE
CONCENTRATION OF HAZARDOUS SUBSTANCE: NOT APPLICABLE
REPORTABLE QUANTITY OF PRODUCT: NOT APPLICABLE

COMMENTS: PRODUCT CONTAINS NO INGREDIENT SUBJECT TO D.O.T OR E.P.A. CERCLA/SARA ENVIRONMENTAL RELEASE REPORTING REGULATIONS. SEE SEC. XI FOR ADDITIONAL SARA COMPLIANCE INFORMATION.

DOW CORNING CORPORATION
MATERIAL SAFETY DATA SHEET

DOW CORNING(R) 100% SILICONE SEALANT, CLEAR

PAGE: 5

SECTION IX - ROUTINE HANDLING PRECAUTIONS

PROTECTIVE EQUIPMENT:

EYES: USE PROPER PROTECTION -- SAFETY GLASSES, AS A MINIMUM.

SKIN *: WASHING AT MEALTIME AND END OF SHIFT IS ADEQUATE. REMOVE CONTAMINATED CLOTHING AND SHOES AS SOON AS PRACTICAL AND CLEAN THOROUGHLY BEFORE REUSE.

INHALATION: USE RESPIRATORY PROTECTION UNLESS LOCAL EXHAUST VENTILATION IS ADEQUATE OR AIR SAMPLING DATA SHOWS EXPOSURES ARE WITHIN TLV AND PEL GUIDELINES.

VENTILATION:

LOCAL EXHAUST: MAY BE NEEDED.
MECHANICAL (GENERAL): RECOMMENDED

SUITABLE RESPIRATOR: ACID GAS/ORGANIC VAPOR TYPE.

THESE PRECAUTIONS ARE FOR ROOM TEMPERATURE HANDLING; USE AT ELEVATED TEMPERATURES, OR AEROSOL/SPRAY APPLICATIONS, MAY REQUIRE ADDED PRECAUTIONS. * GOOD PRACTICE REQUIRES THAT GROSS AMOUNT OF ANY CHEMICAL BE REMOVED FROM THE SKIN AS SOON AS PRACTICAL, ESPECIALLY BEFORE EATING OR SMOKING.

COMMENTS: AVOID BREATHING VAPORS AND EYE AND SKIN CONTACT. USE ONLY WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY.

SECTION X - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: STORE BELOW 90 F/32 C. USE REASONABLE CARE AND CAUTION. KEEP CONTAINER CLOSED.

OTHER PRECAUTIONS: PRODUCT FORMS ACETIC ACID (HOAC) WHEN EXPOSED TO WATER OR HUMID AIR. PROVIDE VENTILATION DURING USE TO CONTROL HOAC EXPOSURE WITHIN SEC. II LIMITS OR USE RESPIRATORY PROTECTION.

COMMENTS: NONE.

SECTION XI - COMMENTS

ADDITIONAL SARA REGULATORY COMPLIANCE INFORMATION

SEC. 312 HAZARD CLASS: IMMEDIATE.

SEC. 313 NOTIFICATION: NOT APPLICABLE - EITHER NONE PRESENT OR NONE PRESENT IN REGULATED QUANTITIES.



DOW CORNING CORPORATION
MATERIAL SAFETY DATA SHEET

DOW CORNING(R) 100% SILICONE SEALANT, CLEAR

PAGE: 6

SECTION XII - COMMENTS

SUPPLEMENTAL STATE COMPLIANCE INFORMATION

PENNSYLVANIA:	8x	7631869	SILICA, AMORPHOUS
		70131678	POLYDIMETHYLSILOXANE, HYDROXY-TERMINATED
MASSACHUSETTS:	8x	7631869	SILICA, AMORPHOUS
NEW JERSEY:	8x	7631869	SILICA, AMORPHOUS, FUMED, #1655
4253343			69430246 DIMETHYL CYCLOSILOXANES
17689779			70131678 POLYDIMETHYLSILOXANE, HYDROXY-TERMINATED
			METHYLTRIACETOXYSILANE
			ETHYLTRIACETOXYSILANE

THESE DATA ARE OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCT SPECIFICATION. NO WARRANTY, EITHER EXPRESSED OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE AND DETERMINE WHETHER THEY ARE APPROPRIATE.

PREPARED BY: JACK L. SHENEGER
LAST REVISION DATE: MARCH 15, 1993
PREVIOUS REVISION DATE: JUNE 1, 1992
DATE: MAY 08, 1993

(R) INDICATES REGISTERED OR TRADEMARK OF THE DOW CORNING CORPORATION.



DOW CORNING CORPORATION
MATERIAL SAFETY DATA SHEET

MATERIAL NAME: DOW CORNING(R) 100% SILICONE SEALANT, WHITE, 8646
EMERGENCY TELEPHONE NO. (517) 496-5900

SECTION I - GENERAL INFORMATION

MANUFACTURER'S NAME: DOW CORNING CORP. PRODUCT INFORMATION NO. (517) 496-6000
ADDRESS: SOUTH SAGINAW ROAD, MIDLAND MI 48686

PROPER SHIPPING NAME(49CFR 172.101); NONE
D.O.T. HAZARD NAME(49CFR 172.101); NONE
D.O.T. ID NO(49CFR 172.101); NONE
D.O.T. HAZARD CLASS(49CFR 172.101); NONE
RCRA HAZARD CLASS(40CFR 261)(IF DISCARDED); NONE
E.P.A. PRIORITY POLLUTANTS(40CFR 122.53); NONE
NFPA = NATIONAL FIRE PROTECTION ASSOCIATION - 704
HEALTH (NFPA); 1 FLAMMABILITY (NFPA); 1 REACTIVITY (NFPA); 0
CAS NO: MIXTURE DOW CORNING WARNING CODE: NOT USED
GENERIC DESCRIPTION: SILICONE

SECTION II - HAZARDOUS INGREDIENTS AS DEFINED IN 29 CFR 1910.1200
(CARCINOGENS IDENTIFIED WITH AN ASTERISK *)

CAS NO.	INGREDIENT	WT.%	EXPOSURE LIMITS
004253343	METHYLTRIACTOXYLSILANE	2	SEE COMMENT BELOW.
017689779	ETHYLTRIACTOXYLSILANE	2	SEE COMMENT BELOW.
007631869	SILICA, AMORPHOUS	8	OSHA PEL; TWA 6 MG/M3 ACGIH TLV; TWA 10 MG/M3 TOTAL DUST

COMMENT: OBSERVE LIMITS FOR ACETIC ACID, FORMED DURING CURING ON EXPOSURE TO WATER OR HUMID AIR. OSHA PEL; TWA 10 PPM. ACGIH TLV; TWA 10 PPM, STEL 15 PPM.



DOW CORNING CORPORATION
MATERIAL SAFETY DATA SHEET

MATERIAL NAME: DOW CORNING(R) 100% SILICONE SEALANT, WHITE, 8646

SECTION III - EFFECTS OF OVEREXPOSURE

EYE: DIRECT CONTACT IRRITATES SLIGHTLY TO MODERATELY WITH REDNESS AND SWELLING.

SKIN: A SINGLE SHORT EXPOSURE (LESS THAN 24 HOURS) MAY IRRITATE. REPEATED PROLONGED CONTACT (24 TO 48 HOURS) MAY IRRITATE MODERATELY.

INHALATION: VAPOR OVEREXPOSURE MAY IRRITATE EYES, NOSE AND THROAT.

ORAL: SMALL AMOUNTS TRANSFERRED TO THE MOUTH BY FINGERS DURING USE, ETC., SHOULD NOT INJURE. SWALLOWING LARGE AMOUNTS MAY CAUSE DIGESTIVE DISCOMFORT.

COMMENTS: NO KNOWN ADVERSE CHRONIC HEALTH EFFECTS, BUT UNNECESSARY EXPOSURE TO ANY CHEMICAL SHOULD BE AVOIDED. THIS PRODUCT, AS WITH ANY CHEMICAL, MAY ENHANCE ALLERGIC CONDITIONS ON CERTAIN PEOPLE. WE DO NOT KNOW OF ANY MEDICAL CONDITIONS THAT MIGHT BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT. NO INJURY FROM DUSTS SHOULD OCCUR DURING REASONABLE USE. IF USE CREATES RESPIRABLE PARTICLES, SOME RESPIRATORY SYSTEM INJURY MAY OCCUR.

SECTION IV - EMERGENCY AND FIRST AID PROCEDURES

EYES: IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES.

SKIN: WIPE OFF AND FLUSH WITH WATER. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS.

INHALATION: REMOVE TO FRESH AIR.

ORAL: NO FIRST AID SHOULD BE NEEDED.

COMMENT: NONE.

SECTION V - FIRE AND EXPLOSION DATA

FLASH POINT (METHOD USED): OPEN CUP ABOVE 250F/120C

AUTOIGNITION: NOT DETERMINED

FLAMMABILITY LIMITS IN AIR: LOWER:N.D. UPPER:N.D.

EXTINGUISHING MEDIA: WATER WATER FOG X CO2 X DRY CHEMICAL X FOAM X OTHER

SPECIAL FIRE FIGHTING PROCEDURES: SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING SHOULD BE WORN IN FIGHTING FIRES INVOLVING CHEMICALS

UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE.

COMMENTS: N.D.=NOT DETERMINED.



DOW CORNING CORPORATION
MATERIAL SAFETY DATA SHEET

MATERIAL NAME: DOW CORNING(R) 100% SILICONE SEALANT, WHITE, 8646

SECTION VI - PHYSICAL DATA

BOILING POINT(AT 760 MM HG): NOT APPLICABLE
SPECIFIC GRAVITY (AT 77 DEG F/25 DEG C): 1.04
MELTING POINT: NOT APPLICABLE
VAPOR PRESSURE (AT 77 DEG F/25 DEG C): LESS THAN 5 MM
VAPOR DENSITY (AIR = 1 AT 77 DEG F/25 DEG C): ABOVE 1
PERCENT VOLATILE BY WEIGHT (%): LESS THAN 5
EVAPORATION RATE (ETHER = 1): NOT APPLICABLE
SOLUBILITY IN WATER(%): LESS THAN 0.1
ODOR, APPEARANCE, COLOR: ACETIC ACID-LIKE, PASTE, WHITE.

NOTE: THE ABOVE INFORMATION IS NOT INTENDED FOR USE IN PREPARING PRODUCT SPECIFICATIONS. CONTACT DOW CORNING BEFORE WRITING SPECIFICATIONS.

SECTION VII - REACTIVITY DATA

STABILITY: STABLE

INCOMPATIBILITY(MATERIAL TO AVOID): OXIDIZING MATERIAL CAN CAUSE A REACTION.
AIR OR MOISTURE CAUSES CURING AND ACETIC ACID VAPORS TO FORM.

CONDITIONS TO AVOID: EXPOSURE TO AIR OR MOISTURE UNTIL READY TO USE.

HAZARDOUS DECOMPOSITION PRODUCTS: SILICON DIOXIDE, CARBON DIOXIDE, AND TRACES OF INCOMPLETELY BURNED CARBON PRODUCTS.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

CONDITIONS TO AVOID: NOT APPLICABLE.

COMMENTS: NONE



DOW CORNING CORPORATION
MATERIAL SAFETY DATA SHEET

MATERIAL NAME: DOW CORNING(R) 100% SILICONE SEALANT, WHITE, 8646

SECTION VIII - SPILL, LEAK, MAINTENANCE/REPAIR AND DISPOSAL PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: REMOVE PRODUCT AND CONTAIN FOR SALVAGE OR DISPOSAL.

PROTECTIVE EQUIPMENT:

EYES: USE PROPER PROTECTION -- SAFETY GLASSES, AS A MINIMUM.

SKIN: WASHING AT MEALTIME OR END OF SHIFT IS ADEQUATE. REMOVE CONTAMINATED CLOTHING AND SHOES AS SOON AS POSSIBLE AND CLEAN THOROUGHLY BEFORE REUSE. RUBBER OR PLASTIC GLOVES ARE RECOMMENDED.

INHALATION: USE RESPIRATORY PROTECTION UNLESS LOCAL EXHAUST VENTILATION IS ADEQUATE OR AIR SAMPLING DATA SHOWS EXPOSURES ARE WITHIN TLV AND PEL GUIDELINES.

WASTE DISPOSAL METHOD: DOW CORNING SUGGESTS THAT ALL LOCAL, STATE AND FEDERAL REGULATIONS CONCERNING HEALTH AND POLLUTION BE REVIEWED TO DETERMINE APPROVED DISPOSAL PROCEDURES. CONTACT DOW CORNING IF THERE ARE ANY DISPOSAL QUESTIONS.

D.O.T. (49CFR 171.8)/E.P.A. (40CFR 117) SPILL REPORTING INFORMATION
HAZARDOUS SUBSTANCE: NONE REPORTABLE QUANTITY: NOT APPLICABLE
CONCENTRATION OF HAZARDOUS SUBSTANCE: NOT APPLICABLE
REPORTABLE QUANTITY OF PRODUCT: NOT APPLICABLE

COMMENTS: PRODUCT CONTAINS NO INGREDIENT SUBJECT TO D.O.T OR E.P.A. CERCLA/SARA ENVIRONMENTAL RELEASE REPORTING REGULATIONS. SEE SEC. XI FOR ADDITIONAL SARA COMPLIANCE INFORMATION.



DOW CORNING CORPORATION
MATERIAL SAFETY DATA SHEET

MATERIAL NAME: DOW CORNING(R) 100% SILICONE SEALANT, WHITE, 8646

SECTION IX - ROUTINE HANDLING PRECAUTIONS

PROTECTIVE EQUIPMENT:

EYES: USE PROPER PROTECTION -- SAFETY GLASSES, AS A MINIMUM.

SKIN *: WASHING AT MEALTIME AND END OF SHIFT IS ADEQUATE. REMOVE CONTAMINATED CLOTHING AND SHOES AS SOON AS POSSIBLE AND CLEAN THOROUGHLY BEFORE REUSE. RUBBER OR PLASTIC GLOVES ARE RECOMMENDED.

INHALATION: USE RESPIRATORY PROTECTION UNLESS LOCAL EXHAUST VENTILATION IS ADEQUATE OR AIR SAMPLING DATA SHOWS EXPOSURES ARE WITHIN TLV AND PEL GUIDELINES.

VENTILATION:

LOCAL EXHAUST: MAY BE NEEDED.
MECHANICAL (GENERAL): RECOMMENDED

SUITABLE RESPIRATOR: ACID GAS/ORGANIC VAPOR TYPE.

THESE PRECAUTIONS ARE FOR ROOM TEMPERATURE HANDLING; USE AT ELEVATED TEMPERATURES, OR AEROSOL/SPRAY APPLICATIONS, MAY REQUIRE ADDED PRECAUTIONS.
* GOOD PRACTICE REQUIRES THAT GROSS AMOUNT OF ANY CHEMICAL BE REMOVED FROM THE SKIN AS SOON AS PRACTICAL, ESPECIALLY BEFORE EATING OR SMOKING.
COMMENTS: AVOID BREATHING VAPORS AND EYE AND SKIN CONTACT. USE ONLY WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY.

SECTION X - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: STORE BELOW 90 F/32 C. USE REASONABLE CARE AND CAUTION. KEEP CONTAINER CLOSED.

OTHER PRECAUTIONS: PRODUCT FORMS ACETIC ACID (HOAC) WHEN EXPOSED TO WATER OR HUMID AIR. PROVIDE VENTILATION DURING USE TO CONTROL HOAC EXPOSURE WITHIN SEC. II LIMITS OR USE RESPIRATORY PROTECTION.
COMMENTS: NONE

SECTION XI - COMMENTS

ADDITIONAL SARA REGULATORY COMPLIANCE INFORMATION

SEC. 312 HAZARD CLASS: IMMEDIATE.

SEC. 313 NOTIFICATION: NOT APPLICABLE - EITHER NONE PRESENT OR NONE PRESENT IN REGULATED QUANTITIES.



DOW CORNING CORPORATION
MATERIAL SAFETY DATA SHEET

MATERIAL NAME: DOW CORNING(R) 100% SILICONE SEALANT, WHITE, 8646

SECTION XII - COMMENTS

SUPPLEMENTAL STATE COMPLIANCE INFORMATION

PENNSYLVANIA:	8%	7631869	SILICA, AMORPHOUS
		70131678	POLYDIMETHYLSILOXANE, HYDROXY-TERMINATED
MASSACHUSETTS:	8%	7631869	SILICA, AMORPHOUS
NEW JERSEY:	8%	7631869	SILICA, AMORPHOUS, FUMED; #1655
		4253343	METHYLTRIAACETOXYSILANE
		17689779	ETHYLTRIAACETOXYSILANE
		63148629	POLYDIMETHYLSILOXANE
			69430246 DIMETHYL CYCLOSILOXANES
			70131678 POLYDIMETHYLSILOXANE, HYDROXY-TERMINATED

THESE DATA ARE OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCT SPECIFICATION. NO WARRANTY, EITHER EXPRESSED OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE AND DETERMINE WHETHER THEY ARE APPROPRIATE.

PREPARED BY: JACK L. SHENEBERGER
LAST REVISION DATE: MAY 29, 1990
PREVIOUS REVISION DATE: SEPTEMBER 19, 1985
DATE: APRIL 13, 1992

(R) INDICATES REGISTERED OR TRADEMARK OF THE DOW CORNING CORPORATION.